

Overhead Projectors

HP-L11CH

Closed head overhead projector

ELMO's HP-L11CH, meets today's toughest demands combining quality images with an irresistible price.



Aperture size	254X254mm(10.0X10.0in.)
Dimensions	Folded: 355x345x235mmx914.0x13.6x9.3in.) Assembled: 355x345x745mm(14.0x13.6x29.3in.) Folded: 355x345x235mmx914.0x13.6x9.3in.) Assembled: 355x345x755mm(14.0x13.6x29.7in.)
Forced air cooling	Forced-air cooling be motor fan
Magnification	x4~ x8
Power consumption	390 W
Power source	AC 120V 60Hz
Projection distance	1.45~2.66m(4.76~8.73ft)
Projection lamp	Supplied with ANSI EYB(82V-360W). An alternative relplacement in EYB-5(86V-360W)which provides extended life with reduces brightness.
Projection lens	290mm(11.4in). Rack and pinion focusing
Safety interlock switch	Built-in safety interlock switch cuts off power when stage frame is opened.
Safety thermal cut-off switch	Built-in safety thermal cut-off switch automatically cuts off power to lamp if projector overheats.
Tilting angle adjustment	Up to 25
Weight	5.7kgs(12.6lbs)
Writing roll attachment	Attachable(option)