

# ELMO

Overhead Projectors

## HP-L3550H DX

### Deluxe overhead projector with lamp changer

Three lamp choices for all types of applications. Economical extended lamp life with ENX-5 lamp (as supplied). Optional replacements: FXL lamp for 4,000 screen lumens or ENX lamp for 3,300 screen lumens



Aperture size	254 x254mm(10.0x10.0in.)
Dimensions	Folded: 330(W)x430(D)x 215(H)mm (13.0x16.9x8.5in.) Assembled:330(W)x430(D)x795(H)mm(13.0x16.9x31.3in.)
Forced-air cooling	Forced-air cooling by motor fan
High/Normal lamp switch	Built-in
Image size	1.0~ 3.0m(3.3~ 9.8ft)
Light output	2,900 lumens w/ENX-5 as supplied 4,000 lumens w/FXL or 3,300 lumens w/ENX
Magnification	x4.0~ x11.8
Power consumption	Max 440W
Power source	AC 120V 60Hz
Projected material	Transparency and roll
Projection distance	1.7~ 4.5m(5.6~ 14.8ft)
Projection lamp	ANSI ENX-5 86V-360W as supplied Optionally, ENX 82V-#^ )W or FXL 82V-410W can be used.
Projection lens	355mm(14.0in.) Rack & pinion focusing 355mm(14.0in.) Rach & pinion focusing 355mm(14.0in.)
Quick lamp change device	Built-in
Safety interlock switch	Built-in safety interlock switch cuts off power when stage frame is opened.
Safety thermal cut-off switch	Built-in safety thermal cut-off switch automatically cuts off power to lamp if projector overheats.
Tilting angle adjustment	Up to 30
Weight	5.9kgs(13.0 lbs)

Writing roll attachment    Attachable(option)