

ELMO

Overhead Projectors

HP-L2900H

Standard overhead projector

Three lamp choices for all types of applications. Economical extended lamp life with ENX-5 lamp (as supplied). Optional replacements: FXL lamp for 4,000 screen lumens or ENX lamp for 3,300 screen lumens.



Aperture size	254x254mm(10.0x10.0in.)
Dimensions	Folded: 330 (W)x430(D)x 215(H)mm (13.0x16.9x8.5in.) Assembled: 330(W)x430(D)x710(H)mm(13.0x16.9x28.0in.)
Forced-air cooling	Forced-air cooling be motor fan
High/Normal lamp switch	Built-in
Image size	1.14~2.51m (3.7~8.2ft)
Light output	2,900 lumens w/ENX-5 as supplied 4,000 lumens w/FXL or 3,300 lumens e/ENX 2,900 lumens w/ENX-5 as supplied 4,00 lumens w/FXL or 3,300 lumens e/ENX
Magnification	x4.5~x9.9 x4.0~x11.8
Power consumption	Max 440W
Power source	AC120V 60Hz
Projected material	Transparency and roll
Projection distance	1.5~3.2m(4.9~ 10.5ft) 1.7~4.5m(5.6~ 14.8ft)
Projection lamp	ANSI ENX-5 86V-360W as supplied Optionally, ENX 82V-360W or FXL 82V-410W can be used.
Projection lens	290mm (11.4in.) Rack & pinion focusing 355mm (14.0in.) Rack & pinion focusing 355mm (14.0in.)
Safety interlock switch	Built-in safety interlock switch cuts off power when stage frame is opened
Safety thermal cut-off switch	Built-in safety thermal cut-off switch automatically cuts off power to lamp if projector overheats.
Tilting angle adjustment	Up to 30

Weight 5.7kgs(12.6 lbs)

Writing roll attachment Attachable(option)