

# ELMO

Overhead Projectors

## HP-L2900H DX

### **Deluxe overhead projector with lamp changer**

Three lamp choices for all types of applications. Economical extended lamp life with ENX-5 lamp (as supplied). Optional replacements: FXL lamp for 4,000 screen lumens or ENX lamp for 3,300 screen lumens



Aperture size	254x254mm(10.0x10.0in.)
Dimensions	Folded: 330 (W)x430(D)x 215(H)mm (13.0x16.9x8.5in.) Assembled: 330(W)x430(D)x710(H)mm(13.0x16.9x28.0in.)
Forced-air cooling	Forced-air cooling my motor fan
High/Normal lamp switch	Built-in
Image size	1.14~2.51m(3.7~8.2ft)
Light output	2,900 lumens w/ENX-5 as supplied 4,000 lumens e/FXL or 3,300 lumens w/ENX
Magnification	x4.5~ x 9.9
Power consumption	Max 440W
Power source	AC 120V 60Hz
Projected material	Transparency and roll
Projection distance	1.5~3.2m(4.9~10.5ft)
Projection lamp	ANSI ENX-5 86V-360W as supplied Optionally, ENX 82V-360W or FXL 82V-410W can be used.
Projection lens	290mm(11.4in.) Rack & pinion focusing
Quick lamp change device	Built-in
Safety interlock switch	Built-in safety interlock switch cuts off power when stage frame is opened.
Safety thermal cut-off switch	Built-in safety thermal cut-off switch automatically cuts off over to lamp if projector overheats.
Tilting angle adjustment	Up to 30
Weight	5.9kgs (13.0 lbs)
Writing roll attachment	Attachable(option)